



LT-200

3D LED tubes



Description

The LT-200 is a pixel tube designed to create immersive outdoor or indoor video and light installations. It is fully prepared for pixel mapping and media control. These transparent IP65-rated LED tubes have a wide viewing angle and they can be used to create alluring 3D spatial effects. This makes them suitable for a wide range of applications, including touring, TV scenography, theme parks, exhibitions, video art, clubs, shopping malls, or just about any fixed or temporary installation.

Features and benefits

- ✓ IP65 RGB pixel 3D graphic LED tube
- ✓ 2 x 130° viewing angle
- ✓ 35mm pixel pitch
- ✓ Practically maintenance-free
- ✓ 2 x 54 pixels per tube
- ✓ DMX control through TLD-612A / ILD
- ✓ 2-meter length per tube
- ✓ Up to 162 controllable DMX channels


Certifications & classifications

IP65

RoHS

CE





Ø 25

Specification

Optical Data	LED expected lifetime	50,000 hours
	Lightsource	54 x 2 RGB LEDs
	Pixel Pitch	35 mm
Photometric	Efficacy	25 lm/W
	Light output all LEDs on	1020 lm
Physical	IP class	IP65
	Lens material	Standard lens, acrylic tube
	Material	Acrylic and aluminium
	Net dimensions	1951 x 27 mm
	Net dimensions inches	76.9 x 1.1 inches
	Net weight	0.56 kg (1.2 lbs)
Features	Addressable pixels	54
	Dimming	Electronic
	View angle	2 x 130°
Electrical	DC power, nominal	12 VDC
	Typical power consumption	40 W
Programming and Control	DMX channels	162
	Drivers	TLD-612 ILD-612 A ILD
	Protocol	USITT DMX512A
Connections	Data / Power input	Female locking 4-pin RS-765
Installation	Orientation	Any
	Rigging possibilities	Top bracket for hanging
	Safety features	Possibility for safety wire thru top bracket
Thermal	Cooling	Passive
	Humidity (max.)	98 %
	Temperature range, Operating	-40°C to 50°C

Temperature range, Start-up	-20°C to 50°C
Temperature range, Storage	-40°C to 80°C

Included items	Included items	User Manual
Conforms To	CE - 2014/30/EU: EMC Directive	EN 61547 EN 55022 EN 61000-6-3 EN 55024
	RoHS2 Directive	2011/65/EU

NOTES:

Due to continuous improvements and innovations, specifications may change without notice.

LEDs' expected lifetime provided by manufacturer and obtained under manufacturer's test conditions.

Zoom range defined as a minimum beam angle to a maximum field angle.

Photometric measurements obtained with Goniometer Scan / SGM Illumination Lab 1.6.0.0.

Lumen output in pixel products is calculated.

Ordering information

Qty	Product name	Item number
☐	LT-200 IP - Led tube 2m (54 pixels)	80080014
☐		
	Accessories	Item number
☐	LT-100/LT-200 Extension Cable (1.5m)	83062060
☐	LT-100/LT-200 Extension Cable (2m)	83062059
☐	LT-100/LT-200 Extension Cable (3m)	83062062
☐	LT-100/LT-200 Extension Cable (0.85m)	83062061
☐	ILD	80070216
☐	LT-100/LT-200 Extension Cable (5m)	83062063
☐		



SGM Light A/S

Headquarter [+45 70 20 74 00](tel:+4570207400)

Mail info@sgmlight.com

Website sgmlight.com