

# iBar 15™

iBar 15™ is a lightweight static IP65 rated 1.000 mm linear bar which uses 15 equally spaced new generation of 30% brighter 15W RGBW multichip LEDs for enhanced 18-bit smooth colour mixing and linear dimming without RGB 'breakup' or grey shadows.

**Light source**

15x 15W RGBW LED multichips

**Light output**

5.920 lx @ 5 m / 6.280 lm

**Zoom range**

7.5° + optional diffusers

**Effects**

pixel control, colour rainbow effect, pre-programmed colours and whites



A fixed 7.5° but redefinable beam angle offers optional diffusers, now with a new system of split filters allowing three different beam angles per entire iBar and generating asymmetrical light output for use as a high-quality cyc light. Optional barn door can trim the beam if required. The advanced pixel control based driver software provides special features including a virtual colour wheel with pre-programmed colours and a set of true whites with CTO Tungsten lamp emulation and more. The practical and highly readable small display provides a menu with personality settings plus DMX and RDM protocols.

The two combined feet / brackets can now be easily adjusted by sliding them in the profile at the back of bar to fit various different types of trusses without using any tools.

# Technical Specification

## Source

- Light source type: 15x 15W RGBW LED multichips
- LED life expectancy: min. 60 000 hours
- Typical lumen maintenance: L70/B50 @ 50.000 hours
- LED colour variants: RGBW

## Optical system

- Beam angle: 7.5° (without diffuser), diffuser 35°x70° included as standard
- Optional diffusers: 32°, 50°, 10°x30°, 30°x10°, 70°x35°
- Fixture total lumen output:
  - 6.280 lm (integrating sphere)
  - 5.041 lm (goniophotometer)
- Brightness: 5920 lx @ 5m

## Dynamic Effects and Features

- Variable CTO: 0-100%
- Virtual Colour Wheel: With 237 colours including whites (2.700 K, 3.200 K, 4.200 K, 5.600 K and 8.000 K)
- Tungsten lamp effect at whites: 2.700 K and 3.200 K (red shift and thermal delay during dimming)
- Colour rainbow effect with variable speed
- Pre-programmed pixel effects with colour, dimming and strobe chases, waves and pulses at variable speed and direction
- Strobe effect: variable speed (max. 20 flashes per second)
- Pre-programmed random strobe & pulse effects
- High resolution electronic dimming: 0-100%
- L3™ - (Low Light Linearity) Imperceptible 18 bit dimming for ultra smooth fade to black

## Control and programming

- Setting & Addressing: 4-segment LED display & 4 control buttons, stand-alone operation with 1 editable program up to 35 steps)
- Protocols: USITT DMX-512, RDM
- Wireless CRMX™ technology from Lumen Radio - on request
- DMX Protocol modes: 4 including SunStrip emulation mode (Halogen Strip)
- Control channels: 16, 11, 61, 76
- Colour mixing: RGBW or CMY
- Manual control of all effects via control panel

## Thermal specification

- Maximum ambient temperature: 40°C (104°F)
- Maximum surface temperature: 80°C (176°F)

## Electrical specification and connections

- Power supply: Electronic auto-ranging
- Input voltage range: 100-240 V, 50/60 Hz
- Power consumption: max. 170 W
- DMX and RDM data in/out: DMX outdoor cables CA-0611 (300mm) + NC5MX-HD/NC5FX-HD (5-pin connectors)
- Power in/out connector: Neutrik powerCON TRUE1 in/out

## Approvals

- CE Compliant
- cETLus Compliant

## Mechanical specification

- Height: 182 mm (7.2")
- Width: 997 mm (39.3")
- Depth: 180 mm (7.1")
- Weight: 11.1 kg (24.5 lbs)
- LED module "tilt" adjustment range: -100/+45°
- Ingress protection rating: IP65

## Rigging

- 2x Omega adaptors with 1/4-turn quick locks

## Included items

- User Manual
- Omega Adaptor CL-regular 2 pcs: 10980033
- Diffusion filter: 35° x 70° 10980247
- Cap for XLR connector: 19020175

## Optional accessories

- Diffusion filter:
  - 35° x 70° 10980247
  - 10° x 30° 10980248
  - 70° x 35° 10980249
  - 30° x 10° 10980250
  - 50° 10980251
  - 32° 10980252
  - Cyc Light kit 10980422
- Gel Frame set: 10980269
- Barndoor: 10980421
- Slim Mounting Brackets for iBar15, 2pcs: 10980625
- Doughty Trigger Clamp: 17030386
- Safety wire 36 kg: 99011963
- Mains Cable powerCON TRUE1 In/Schuko, 2m, Indoor: 13052405
- Mains Cable powerCON TRUE1 In/US, 2m, Indoor: 13052406
- Daisy Chain powerCON TRUE1 In/Out, EU, 2m, Indoor: 13052439
- Mains Cable powerCON TRUE1 In/CEE 16A, 2m, Indoor: 13052445
- Mains Cable powerCON TRUE1 In/Open ended, 2m, Indoor: 13052407
- Mains Cable powerCON TRUE1 In/open ended, 2m EU, outdoor: 13052276
- Mains Cable powerCON TRUE1 In/open ended, 2m US, outdoor: 13052277
- Daisy Chain powerCON TRUE1 In/Out, US, 2m, Outdoor: 13052280
- Daisy Chain powerCON TRUE1 In/Out, EU, 2m, Outdoor: 13052281
- Daisy Chain powerCON TRUE1 In/Out, US, 2m, Indoor: 13052440
- Daisy Chain powerCON TRUE1 In/Out, EU, 5m, Indoor: 13052444
- Daisy Chain powerCON TRUE1 In/Out, EU, 0,75m, Outdoor: 13052278
- Daisy Chain powerCON TRUE1 In/Out, US, 0,75m, Outdoor: 13052279
- Single Top Loader Case: 10120184
- Quad Top Loader Case: 10120185

## Legal

- iBar 15™ is a Trademark of Robe lighting s. r. o.
- iBar 15™ is patented by Robe lighting s. r. o. and is protected by one or more pending or issued patents