



P-5 W

White LED Wash Light



Description

The P-5 W is a white output version of the color P-5, which is the most well-known and reputed IP65 LED wash in the lighting industry. It is perfect for creating even coverage at a high light output. The P-5 W uses 16bit dimming performance, it is completely upgradeable through firmware updates and it offers a full variety of beam angles for medium throws via interchangeable lenses.

Features and benefits









- ✓ High-performance IP65 white LED light source
- ✓ 43°, 21°, and 15° interchangeable lenses
- ✓ DMX, RDM, and wireless control
- ✓ Practically maintenance-free
- ✓ 6400K color temperature
- ✓ 23700 lumens in 435W
- ✓ Accurate 16bit dimming performance
- ✓ Flicker-free / Programmable scenes

Certifications & classifications

IP65

RoHS





Specification

Optical Data	LED expected lifetime	50,000 hours
	Lens	15° 21° 43°
	Lightsources	44 x high-power 10W cool white LEDs (6,400K)
Photometric	Beam angle(s)	14° (with 15° lens) 26° (with 21° lens) 35° (with 43° lens)
	Color Temperature	6400K
	Efficacy	56 lm/W
	Light output all LEDs on	23700 lm
	Maximum Field Angle	79 °
	Minimum Field Angle	33 °
Physical	Color options	Black - RAL 9004 Custom color - Any RAL White - RAL 9010
	IP class	IP65
	Lens material	PE and tempered glass front
	Material	Aluminium
	Net dimensions	497 x 268 x 122 mm
	Net dimensions inches	19.6 x 10.6 x 4.8 inches
	Net weight	8.9 kg (19.6 lbs)
Features	Dimming	Electronic
	Strobe	Ultra-high-speed strobe effects
	Tilt	0 - 190°
Electrical	AC power, max.	190 - 264V 50/60Hz
	AC Power, nominal	208 - 240V 50/60Hz
	Electrical Protection	Overload protection
	Max Inrush Current	45 A
	Max power consumption	470 W
	Power factor	0.99 PF (230 V)
	Power Supply Unit	Auto-ranging electronic switch-mode
	Standby power consumption	8 W
	Typical power consumption	435 W

Programming and Control	16-bit control	Dimmer
	Cabled DMX	5 pin XLR input/output
	DMX channels	1 or 2
	DMX modes	2
	Protocol	USITT DMX512A Wireless DMX (LumenRadio) RDM ANSI E1.20
	Setting and addressing	OLED graphical display / 4 buttons RDM ANSI E1.20 RFID Standalone mode
Connections	Standalone mode	Quick Color Standalone mode programmable via RFID Up to 24 programmable scenes
	Wireless DMX	Lumen Radio with RDM
	DMX data in/out	IP65 XLR 5-pin cable 0.5m
	Power	Power cable 1 meter with bare ends
Installation	Mounting point	2 x 2 quarter-turn locking points for one or two Omega brackets
	Orientation	Any
	Rigging possibilities	Floor stand (included) or hanging (Omega clamps included)
	Safety features	Bottom mount for safety wire Minimum distance to combustible materials: 0.3 meter (11 in).
Thermal	Cooling	Active, Forced Air, Temperature- regulated
	Humidity (max.)	98 %
	Temperature range, Operating	-40°C to 50°C
	Temperature range, Start-up	-20°C to 50°C
	Temperature range, Storage	-40°C to 80°C
	Thermal Protection	Automatic overtemperature protection
Included items	Included items	Wireless DMX antenna Mounting bracket (incl. screws) 2 Omega bracket with quarter-turn fasteners Safety instructions and installation quick guide
Conforms To	CE - 2014/30/EU: EMC Directive	EN 55103-1 EN 55103-2 EN 55015 EN 61547

		EN 61000-3-2 EN 61000-3-3
	CE - 2014/35/EU: Low Voltage Directive	EN 60598-1 EN 60598-2-17 EN 62471 EN 60529
	RoHS2 Directive	2011/65/EU
	UL	UL Std. 1573
Certified To	CSA	CSA Std. C22.2 No. 166

NOTES:

Due to continuous improvements and innovations, specifications may change without notice.

LEDs' expected lifetime provided by manufacturer and obtained under manufacturer's test conditions.

Zoom range defined as a minimum beam angle to a maximum field angle.

Photometric measurements obtained with Goniometer Scan / SGM Illumination Lab 1.6.0.0.

Lumen output in pixel products is calculated.

Ordering information

Qty	Product name	Item number
☐	P-5 W Wash, 15deg, Std, BL	80030516
☐	P-5 W Wash, 21deg, Std, BL	80030520
☐	P-5 W Wash, 43deg, Std, BL	80030521
☐		
	Accessories	Item number
☐	P-5 Lens Kit, 15°	83061116
☐	P-5 Lens Kit, 21°	83061117
☐	P-5 Lens Kit, 43°	83061118
☐	BCC-2 Dual Bracket	83060603
☐	BCC-4 Quad Bracket	83060604
☐	Omega Bracket with 1/4-turn fasteners	83060602
☐	4-way Barndoors for P-5, i-5, X-5, Q-7	83061120
☐	8-way Barndoors for P-5, i-5, X-5, Q-7	83061121
☐	Accessory Holder for P-5 & i-5	83061119
☐	Color Frame for P-5, Q-7, X-5, i-5	83061122
☐	Floor Stand for P-5, X-5 & Q-7	83060610
☐	Flight Case for 4 pcs of P-5/Q-7/X-5	82051501
☐	Flight Case for 4 pcs of P-5/Q-7/X-5 incl. barndoors	82051502
☐	SGM USB uploader cable	83062011
☐	Vacuum Test Kit	83061136
☐	A-4	80070217
☐	Omega Bracket POI	83060623
☐	Diffusion filter for P-5, i-5 - elliptical horizontal, external	83061027
☐	Diffusion filter for P-5, i-5 - elliptical vertical, external	83061028
☐	Diffusion filter for P-5, i-5 - medium, external	83061025
☐	Diffusion filter for P-5, i-5 - wide, external	83061026
☐	RDM Addressing Tool	
☐		



SGM Light A/S

Headquarter [+45 70 20 74 00](tel:+4570207400)

Mail info@sgmlight.com

Website sgmlight.com